

WIRE SPIRAL**855AA****FLEXOR 4SH MSHA****EN 856 4SH**

Tube	OIL RESISTANT SYNTHETIC RUBBER
Reinforcement	FOUR HIGH TENSILE STEEL SPIRALS (4S)
Cover	ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER
Application	VERY HIGH PRESSURE HYDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER.
Constant operation	-40°C +100°C
Ambient temperature	-40°C +80°C
Fittings	Consult fittings catalogue
Length	Random up to 1" - 40 m max over 1"
Branding	ALFAGOMMA FLEXOR 4SH ID... - WP ... MPa (... PSI) - EN 856 4SH DN... - USMSHA IC-152/8 - ... - Q/yr
Note	S.F.: 4:1

Code	ID mm	ID in	Dash	OD mm	OD in	WP Mpa	WP psi	BP Mpa	BP psi	BR mm	BR in	Weight kg/m	Weight lb/C ft
855AA02000RFB8	19	3/4	-12	32,2	1,27	42	6000	168	24000	280	11,2	1,57	106
855AA02500RFB8	25	1	-16	38,7	1,52	38	5500	152	22000	340	13,6	1,95	131
855AA03200RFB8	32	1.1/4	-20	45,5	1,79	35	5000	140	20000	460	18,4	2,47	165
855AA03800RFB8	38	1.1/2	-24	53,5	2,11	29	4200	116	16800	560	22,4	3,27	219
855AA05100RFB8	51	2	-32	68,1	2,68	25	3650	100	14600	700	28	4,67	313