

Concrete**T-740 AA****CONCRETE PUMPING 85 BAR (1275 PSI) - HEAVY DUTY - STEEL REINFORCED**

TUBE	BLACK CONDUCTIVE NR - ABRASION RESISTANT
REINFORCEMENT	HIGH TENSILE STEEL CORDS
COVER	BLACK CONDUCTIVE SBR/NR - ABRASION AND OZONE RESISTANT
APPLICATION	HIGH PRESSURE CONCRETE PUMPING.
SAFETY FACTOR	2:1
TEMPERATURE	-30°C +80°C (-22°F +176°F)
BRAND TEXT	ALFAGOMMA -ITALY- T-740 85 BAR (1275 PSI) W.P. HEAVY DUTY CONCRETE PUMPING (omega)
BRAND TYPE	YELLOW LETTERS
APPROVALS	
NOTE	

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
740AA0516977N0	51	2"	69	9	2160	85	1275		255	15,25/20/61	61
740AA0638577N0	63	2" 1/2	85	11	3380	85	1275		265	20/61	61
740AA0760077N0	76	3"	100	12	4590	85	1275		380	15,25/20/30,5	20
740AA0901677N0	90	3" 1/2	116	13	5930	85	1275		450	20	
740AA1022877N0	102	4"	128	13	7510	85	1275		510	15,25/20/30,5	20
740AA1275577N0	127	5"	155	14	10940	85	1275		635	15,25/20	20
740AA1528677N0	152	6"	186	17	14250	85	1275		760	20	