

GATES S-SERIES WATER DISCHARGE HOSE <> SWR-150D (150 PSI) 102000-RWS

Recommended For: Used in water transfer

Temperature Range: -4°F to +185°F [-20°C to +85°C]

Tube: Black NR/SBR blended

Reinforcement: High strength textile fabric

Design Factor: 3:1

Cover: Black NR/SBR or EPDM

Branding: Continuous transfer. Example: "SWR-150D WATER DISCHARGE HOSE 150 PSI [10.3 Bar]"



PRODUCT CODE	ID (INCH)	OD (MM)	WP (PSI)	SAFETY FACTOR	LENGTH (FT)	COVER	LIST PRICE [US\$/FT]
16SWR-150D	1	20.5	150	3:1	200	BLACK	2.53
32SWR-150D	2	64	150	3:1	200	BLACK	7.62
48SWR-150D	3	89	150	3:1	200	BLACK	10.83
64SWR-150D	4	117	150	3:1	200	BLACK	15.03
80SWR-150D	5	146	150	3:1	200	BLACK	27.58
96SWR-150D	6	171	150	3:1	200	BLACK	32.54
128SWR-150D	8	225	150	3:1	100	BLACK	56.55
160SWR-150D	10	280	150	3:1	100	BLACK	91.08
192SWR-150D	12	333	150	3:1	39	BLACK	113.70