

For Earth, For Life
Kubota

KUBOTA DIESEL TRACTOR

B

B2420

Kubota's compact, versatile and strong B2420 is the ideal workhorse for paddy fields and dry fields.



SPECIFICATIONS

B2420



| | | | | | |
|--|---|-----------------------------------|-------------|--|------------------------------|
| Dimensions | Overall Length | | mm | 2140 | |
| | Overall Width | | mm | 1015 | |
| | Overall Height (Top of ROPS/Canopy) | | mm | 2167 | |
| | Wheelbase | | mm | 1563 | |
| | Ground Clearance (Lowest Point) | | mm | 325 | |
| Weight | | | kg | 595 | |
| Engine | Maker | | | Kubota | |
| | Country of Manufacturer | | | Japan | |
| | Model | | | D115-E2-D221 | |
| | Type | | | E-TVCS, Liquid-Cooled, 3-Cylinder Diesel | |
| | Aspiration | | | Naturally Aspirated | |
| | Engine Gross Power | | hp (kW) | 24 (32.17) | |
| | Rated Engine Speed | | rpm | 2600 | |
| | Number of Cylinders | | | 3 | |
| | Bore x Stroke | | mm (in) | 78 x 78.4 (3.07 x 3.09) | |
| Displacement | | cc (cu in) | 1123 (68.5) | | |
| Power Take-Off (PTO) | PTO Power | | hp (kW) | 19.2 (25.74) | |
| | Number of PTO Shaft Spline | | | 6 | |
| | PTO Speeds @ Engine Speed | | | 540 (2600), 960 (2552) | |
| Fuel System | Fuel Tank Capacity | | L | 26 | |
| Air Cleaner | Pre-Cleaner | | | Double Element | |
| Electrical System | Battery | | V | 12 | |
| Instruments | Hour Meter | | | Electrical | |
| | Engine Speed Indicator | | | Electrical | |
| | Fuel Gauge | | | Electrical | |
| | Temperature Gauge | | | Electrical | |
| | Ammeter Warning Lights | | | Electrical | |
| | Oil Pressure Warning Lights | | | Electrical | |
| | Battery Charging Light | | | Electrical | |
| Travelling System | Clutch | Type | | Dry Single Plate | |
| | | Type | | Gear Shift | |
| | Transmission | Number of Forward Speeds | | | 9 |
| | | Number of Reverse Speeds | | | 3 |
| | | Road Speed Range (Min. - Max.) | km/h | | 1.2 - 18.8 |
| | Steering | Type | | | Integral Type Power Steering |
| Brake | Type | | | Wet Disc | |
| | Turning Radius | With Brake | m | 2.1 | |
| Hydraulic System | Main (Implement) Pump Flow | | L/min | 16.6 | |
| | Steering Pump Flow | | L/min | 9.8 | |
| | 3-Point Linkage, Category | | | Category I | |
| | Maximum Lift Capacity | @ Ball Ends with Arms Horizontal | kg (lbs) | | 750 (1650) |
| | | @ 610 mm (24 in) Beyond Ball Ends | kg (lbs) | | 590 (1298) |
| | Lift Controls (Draft, Position, and/or Mix) | | | Position Control | |
| Agricultural Tire Size and Ply Rating | Front | | | 7 -- 12 | |
| | Rear | | | 8.3 -- 20 | |

Kubota Philippines, Inc.

Manila Head Office:

232 Quirino Highway, Baesa, Quezon City,
Metro Manila
Tel. Nos.: (632) 4223500 to 03
Fax Nos.: (632) 4223504 to 05
E-mail: kpi@kubota.com.ph
Website: www.kubota.com.ph

Davao Branch:

Crossing Ma-a, C. P. Garcia Highway,
Davao City 8000
Tel. Nos.: (082) 2828160 to 61
E-mail: kpidavao@kubota.com.ph

Authorized Dealer: