

DC-35

For Earth, For Life
Kubota

Combine Harvester *For Rice*



COMPACT YET FULLY FEATURED

OUTSTANDING FEATURES

- IDEAL FOR HARVESTING SMALL PADDY FIELDS
- EXCEPTIONAL OPERATIONAL PERFORMANCE UNDER HIGH LOAD CONDITIONS
- OUTSTANDING THRESHING AND SEPARATION PERFORMANCES
- EASY OPERATION
- EASY MAINTENANCE

Exceptional Operational Performance



SPECIFICATIONS

Dimensions	Length	mm	4120	
	Width	mm	1850	
	Height	mm	2150	
Weight		kg	1550	
Engine	Model		Kubota D1105-T-E2-C-1	
	Type		Water-cooled, 4-Cycle, 3-Cylinder, Vertical Diesel Engine (with Turbocharger)	
	Displacement	L	1.123	
	Output/Rotation Speed	kW(PS)/rpm	24.5 (33.3) / 3000	
	Fuel Tank Capacity	L	60	
Travel Section	Crawler	Width x Ground Contact Length	mm	400 x 1330
		Center Distance	mm	940
		Average Ground Pressure	kPa(kgf/cm ²)	14.3 (0.146)
		Minimum Ground Clearance	mm	300
	Speed Shift System			Hydrostatic Variable Speed (HST)
	Travel Speed	Forward	m/s	Low: 0 - 0.70
Backward		m/s	High: 0 - 1.10	
Turning System			Clutch and Break	
Reaper Section	Reel	Diameter x Width	mm	800 x 1420
		Up/Down Control		Hydraulic System
	Cutter Bar Length	mm	1448	
Thresher Section	Threshing System			Axial Flow System (Threshing Tooth System)
	Threshing Cylinder	Diameter x Length	mm	545 x 1520
		Revolutions	rpm	630
	Concave Area	m ²	0.991	
Sorting System			Oscillating / Wind Force (Adjustable Chaffer Sieve)	
Hopper	Capacity	L	130	
	Take-out System			2 / Bagging
Electrical System			12 Volts Battery Starting, Lighting Equipment, and Alarms (Coolant Temperature, Engine Oil Pressure, & Hopper Full)	
Harvesting Capacity		ha/hr	0.1 - 0.27 (Rice)	

KUBOTA Philippines, Inc.

Manila Head Office:

232 Quirino Highway, Baesa, Quezon City, Metro Manila
Tel. Nos.: (632) 4223500 to 03; Fax Nos.: (632) 4223504 to 03
E-mail: kpi_g.kpi@kubota.com

Davao Branch:

1 Yuta@Dabaw Bldg., Purok 38, Diversion Road, Ma-a, Davao City 8000
Tel. Nos.: (082) 2828160 to 61

Website: www.kubota.com.ph

Authorized Dealer: