

For Earth, For Life
Kubota

KUBOTA DIESEL TRACTOR

L

L5018

All the power and versatility you need to handle any job,
from paddy to dry fields.



SPECIFICATIONS

Dimensions	Overall Length	Without 3P	mm	3200	
	Overall Width		mm	1495	
	Overall Height		mm	2049	
	Wheelbase		mm	1925	
	Ground Clearance	Minimum	mm	400	
	Tread Width	Front Wheel		mm	1150
Rear Wheel			mm	1155, 1225	
Weight			kg	1490	
Engine System	Maker			Kubota	
	Model			V2403-M-DI	
	Type			Diesel Engine, Direct Injection, Vertical, 4-Cycle, Water-Cooled	
	Net Power		hp	47	
	Gross Power		hp	50	
	Number of Cylinders			4	
	Bore and Stroke		mm	87 x 102.4	
	Total Displacement		L	2.434	
	Rated Revolution		rpm	2700	
Fuel System	Maximum Torque		N-m	155	
	Fuel Tank Capacity		L	48	
Traveling System and Transmission System	Standard Tire Size	Front	in	8 - 18	
		Rear	in	13.6 - 26	
	Directional Transmission	Type			Synchro Shuttle
	Transmission Speed	Number of Forward Speeds			8
		Number of Reverse Speeds			8
	Power Steering	Type			Standard (Integral)
	Braking System	Type			Wet Disc Type
	Clutch	Type			Dry Type Single Stage
	Minimum Turning Radius	With Brake Assistance	m		2.65
Traveling Speed	Forward	km/h		2.5 - 27.2	
	Reverse	km/h		2.4 - 26.1	
Power Take-Off (PTO) System	Rear PTO Standard Size	in		SAE 1-3/8	
		splines		6	
	PTO Speed	Engine Speed	rpm		540 at 2268 Engine Speed 750 at 2348 Engine Speed
Hydraulic System	Pump Capacity	Main	L/min	30.5	
	Hydraulic Control System	Type		Position Control	
	3-Point Hitch	Type		Category I	
	Maximum Lift Force	At Lift Point	kg		1300
610 mm Behind Lift Point		kg		1053	
Drive Train System				4-Wheel Drive	

SPECIFICATIONS OF FD186F FRONT DOZER

Model		FD186F
Length	mm	1830
Width	mm	512
Weight	kg	450
Blade Lifting Height	mm	>400
Ground Clearance	mm	>350
Lifting Speed	Up (sec)	0.8
	Down (sec)	1
Soil Carrying	kg	≥450

SPECIFICATIONS OF KRX193 ROTARY TILLER

Model			KRX193
Dimensions	Width		2153
	Length	mm	893
	Height		1033
Weight	With Joint	kg	464
Blade Type			Flange
Number of Blade		pcs	36
Tilling Width		mm	1863
Blade Shaft Rotation	PTO 540	rpm	231
	PTO 750	rpm	321

SPECIFICATIONS OF DP224F DISC PLOW

Model		DP224F
Dimensions	Width (mm)	1300
	Depth (mm)	2369
	Height (mm)	1036
Disc Size	in	22
Number of Disc	pcs	4
Disc Type		Special Sharp Edge
Hitch Type		Standard 3-Point Hitch
Weight	kg	315
Lifting Height	mm	≥350
Working Depth	mm	150-200
Working Width	mm	900

SPECIFICATIONS OF DH245-6F DISC HARROW

Model		DH245-6F
Dimensions	Width (mm)	2189
	Depth (mm)	1335
	Height (mm)	1058
Disc Size	in	24
Number of Disc	pcs	5-6
Hitch Type		Standard 3-Point Hitch
Weight	kg	380
Lifting Height	mm	471.6
Working Depth	mm	150-200
Working Width	mm	1100

KUBOTA Philippines, Inc.

Manila Head Office:

232 Quirino Highway, Baesa, Quezon City, Metro Manila
Tel. Nos.: (632) 4223500 to 03; Fax Nos.: (632) 4223504 to 05
E-mail: kpi_g.kpi@kubota.com

Davao Branch:

1 Yuta@Dabaw Bldg., Purok 38, Diversion Road, Ma-a, Davao City 8000
Tel. Nos.: (082) 2828160 to 61

Website: www.kubota.com.ph

Authorized Dealer: