

# ShineVision



## Features

- ▶ RF communication for wireless operation.
- ▶ Automatic monitoring of up to six inverters simultaneously, applicable for small home system.
- ▶ Simple installation. It can be placed anywhere indoor with signal coverage.
- ▶ Easy-to-understand data display by simple key operation: real-time power, three-phase AC voltage, PV voltage, daily, monthly and total power yield and income, temperature, light intensity, the date and time.
- ▶ Data archiving automatically and permanently with high security.
- ▶ Audio alarm in the event of errors.
- ▶ Low power consumption, powered by adaptor or battery.

## GROWATT NEW ENERGY TECHNOLOGY Co.,LTD

A: Building B, Jiayu Industrial Zone, #28 Guanghui Road, Longteng Community, Shiyan, Baoan District, Shenzhen, P.R.China.

T: + 86 755 2747 1900 F: + 86 755 2749 1460 E: info@ginverter.com

## Communication

---

Inverter communication	Wireless radio frequency
Number of inverters	Max.6 units

## Communication range

---

Partition communication	Max.30m
-------------------------	---------

## Power supply

---

Power adapter	Input : 100-240V, 50/60Hz AC Output: 5V/0.1A AC
Type of battery	Number 5 AA alkaline battery

## Environmental conditions for operation

---

Emitter temperature	-10°C ~ 60°C
Monitor temperature	-10 °C ~ 50°C
Humidity range	≤80%
Protection rating	IP20

## General Data

---

Dimensions (W / H / D)	217/150/72mm
Weight	0.82kg
Installation site	Indoor
Deployment options	Desktop device
Language versions	English

## Features

---

Display	LCD display
Operation	key-press
Warranty	13 months

## Information displayed

---

General Information	Time, date, temperature
System Data	AC voltage, PV voltage, daily yield, monthly yield, total yield, etc.