

Chassis

160 x 65 x 8 mm U-shaped channels; side members and crossbars. Tail lights for braking, signaling and reversing can be connected to vehicle wiring system.



Ring Coupler

Forged steel with inside diameter of 70 mm for connecting to hitch of tow vehicle.



Leaf Spring Suspension

The ideal suspension for load bearing trailers. Spreads the weight of load across a wide surface area of the trailer acquiring balance and safety for transport.



Swivel-Type Tongue Jack

Easy operation. Once the coupler and hitch are secured, the jack can be swiveled parallel to the trailer frame away from the roadway.



| General Specifications | |
|------------------------------|---------------|
| Model | PGM-1500 |
| Load Capacity (Tons) | 1.5 |
| Max. Load (Tons) | 2.0 |
| Net Weight (Tons) | 0.55 |
| Max. Speed (Kph) | 30 |
| Tire Type | 6.5 - R15 x 2 |
| Rim Type | 4.5E |
| Generator Application (KVA)* | 15 up to 60 |

Specifications are subject to change without prior notice.

Manufactured by:

Powercity Electromechanical & Equipment Co. Ltd. Laicuo Industrial Zone, Xiyuan Side, Jinjiang City, Fujian, China

Distributed in the Philippines by:

Powercity Corporation

Km. 20, East Service Road, Muntinlupa City

Metro Manila, Philippines

Tel. +63 2 869 1991

Fax. +63 2 869 3869

Email. contactus@powercity.ph Website. www.powercity.ph

Made in China

^{* -} Powercity brand generators.